TECHNICAL DATA SHEET

TrueGrip SUPERIOR CONTACT ADHESIVE

PREMIUM HIGH TEMPERATURE CONTACT ADHESIVE



- High temperature resistance (> 90°C)
- Stronger, more aggressive bond
- Bonds a wide range of materials
- Fast, professional results
- Up to 35% more coverage

PRODUCT DESCRIPTION

TrueGrip Superior is a high-performance contact adhesive from the latest generation of synthetic rubber/resin adhesives. Its high solids, low solvent formulation produces a quicker, stronger and more aggressive bonding system that outperforms many conventional adhesives.

TYPICAL APPLICATIONS

Bonds decorative laminates, foam, felt, fabrics, carpets and carpet tiles, cardboard, rubber, polythene, sheet vinyl and most plastics to themselves, and a wide variety of substrates including wood, particle board, MDF, metal, concrete, brickwork, stone, slate and glass. Ideal for contract flooring, exhibitions, carpet laying, furniture manufacture, re-upholstery, laminating, veneering, shop fitting, joinery and vehicle, boat and caravan fitting.

TECHNICAL DATA

Adhesive type	Synthetic rubber / resin
Solvent	Chlorinated
Solids content	Approx. 29%
Coverage	Up to 35% more than standard sprays
Heat resistance	> 90°C
Shelf life	12 months (unopened)
Pack size	500ml aerosol

Note: Not suitable for heavily plasticised PVC.

DIRECTIONS FOR USE

1. Ensure surfaces are clean, dry and free from dust, grease and loose material.
2. Shake the can well for at least 30 seconds.
3. Hold the can 150–250mm from the surface and apply an even coat to both surfaces.
4. Allow to become touch dry (approx. 1–5 minutes).
5. Bring the surfaces together and press firmly to achieve full contact.

DRYING TIMES

Touch dry: 1–5 minutes
Open time: up to 30 minutes
Full cure: up to 24 hours

STORAGE

Store in a cool, dry place between 5°C and 25°C. Protect from frost and direct sunlight.

PRECAUTIONS

Highly flammable aerosol. Use in a well-ventilated area. Avoid inhalation of spray. Always refer to the Safety Data Sheet (SDS) before use.

PROFESSIONAL SPRAY ADHESVES FOR THE FLOORING INDUSTRY